

Hybrid Intrusion Alarm Panel



Hybrid Intrusion Alarm Panel

XI-PSH02

SALIENT FEATURES

- Hybrid Intrusion Alarm Panel with inbuilt LCD display Keypad, remote & GSM Autodialler or RS485 or RS232
- Total 25 zones (Wireless + Wired)
- 9 wired zone (8zones fully programmable + 1zone for fire detection devices)
- 16 wireless zones
- SMS arming/disarming
- Zone Name Tagging
- 16*2 Backlit LCD + Capacitive touch keypad with 13 keys
- GSM Autodialler: 20 sec voice message to 10numbers (landline/mobile/EPBX) + SMS alert to
- 10mobile numbers
- Arm/disarm/Perimeter Arm modes
- Dures code feature
- Auto Arming
- 100event memory
- Real time clock
- Indication: LED Indication for following a) Zone Trouble b) System Disarmed c) System Armed
- Audio Buzzer Status Indication
- Connectivity: 10/100MBPS Ethernet Port with SIA IP Protocol
- Battery Backup
- Power Supply: Adaptor - 15Vdc/1A
- Dimension: 290x180x40mm (LxHxW)
- Operating Temp: 0°C to 55°C
- Humidity: 0 to 95 % Rh.