

Indoor Mini IR Speed Dome Camera



10x Speed Dome CAMERA

XSD10X01

Xper High Performance Speed Dome Outdoor camera gives high resolution detailed images even in challenging environments. It is equipped with 10x zoom module for performing Pan, Tilt and Zoom operations.

SALIENT FEATURES

- IR distance up to 50 meters; English OSD
- Support ambient light detection, IR Illumination On 1-15 grade selectable
- 128 Presets, Guard Tour 3 groups
- 360°continuous rotation, horizontal :50°/s ,Vertical :30°/s
- Dome ID, baud rate, communication protocol can be changed from OSD
- Supported Protocols: Pelco-D/P
- CE, FCC & RoHS Certified

Specification

Model	XSD10X01
Image Device	1/4 "SONY Ex-View CCD
Lens	10X optics Zoom (F=1.6, f=4.8mm-48mm)
Zoom Module	10X
IR	Dual IR filter switchable Day / Night automatically, 850nm IR filtration ratio>80%
Resolution	480 TVL
Minimum Illumination	Color 0.1Lux(Normal environment), Night 0.01Lux (Real time)
S/N Rate	> 52dB
Electronic Shutter	Auto/ 1/50-1/10000Sec
Back Light Compensation	Auto
Auto Gain	Auto
White Balance	Auto
Video Output	1.0p-p, (75, complex video)
Horizontal Rotation Speed	0.1°-50°/s
Horizontal Rotation Range	360°
Tilt Rotation Range	94°
Auto flip	Horizontal 180°,Vertical 90°
Auto Control IR LED	PWM
A-B Scan	User programmable
A-B Scan Speed	1~64 grade selectable
Dwell Preset	05-60s
Preset Point	128
Go to Preset Speed	50°/s
Guard Tours	3 groups
Guard Points	Max. 16 Points, dwell time user selectable 02~60s
IR Illumination On	1-15 grade selectable
Communication Protocol	Pelco-D, Auto
Communication	RS485
Baud Rate	1200/ 2400/ 4800/ 9600bps
Operating Temperature	Indoor: 0°~+40°
Operating Humidity	≤95% Non Condensing
Power	12V DC
IR Illumination Distance	Up to 50 meters
Power Consumption	≤ 20W
Certification	CE, FCC & RoHS
Note:	Product appearance & technical specifications are subject to change without any prior notice.