

36X Outdoor Speed Camera



36X Outdoor Speed Camera

XSDPRO-36X10

SALIENT FEATURES

- 1/4" Ex-view HAD CCD (SONY) Outdoor Speed Dome Camera.
- Adopting ARM, FPGA and real time OS, excellent stability And reliability.
- Supporting translucent Menu, Graphics OSD function convenient For-customizing homochromous or translucent user logo.
- 0.9 degree precise stepping motor, ensuring image un-dithered at low speed.
- Perpetual calendar function, synchronizing with alarm linkage.
- Auto recovery function from power cut.
- Interior temperature display, deviation within ± 1 degree Celsius.
- Redundant power supply and inner space design convenient OEM project.
- Quick installation structure and separation design for spherical shell And-camera block, convenient for maintenance.
- Support calendar timing event trigger.
- Adopting gas discharging tube and TVS lightning protection for Power-supply, RS485 and video.
- Isolation switches power supply, higher safety performance.
- Rotation speed auto adjustment as per camera zoom times realizing-Accurate object positioning.
- CE, FCC & RoHS Certified

Specification

Model	XSDPRO-36X10
Image Sensor	1/4" Ex-view HAD CCD (SONY)
Minimum Illumination	1.0 LUX /F1.6(Color Mode) 0.1 LUX / F1.6(B/W Mode)
Horizontal Resolution	540 TV Line
Focal Length	3.4 mm~122.4mm
Zoom Ratio	36X optical zoom with auto focus (12X digital zoom)
Panning Angle	360° continuous rotation
Tilt Angle	0°~92°
Preset	220 positions
Patterns	4 Patterns
Tour	4 Guard tour
Auto	Scan 4 Group
Resistance Fog Function	Yes
English / Chinese Menu	Available
Real time clock function	Available
Inside Temperature Display	Available
Speed	0.5°~270° / Sec(Pan) ; 0.5°~90° Sec(Tilt)
Alarm Input / Output	7 Input, 2 relay Output
Operation Temperature	- 40°C ~ 60°C
Power Supply	AC24V , 2A
Certification	CE, FCC & RoHS
Note:	Product appearance & technical specifications are subject to change without any prior notice.