

Value Series

Real Time DVR/HVR



Value Series 16Ch DVR/HVR

XD168V

Xper Value Series Pentaplex DVR provides multi-channel recording with simultaneous playback and viewing. The Xper Value Series DVR can be accessed and controlled from front panel, Network or via a mouse, giving the user full access to all the DVR's features including PTZ control, Alarm and Event Management and Activity Detection.

SALIENT FEATURES

- H.264 High efficiency Video Compression.
- 16CH with total 400fps support (2D1+14CIF)@25FPS/ch.
- 16CH playback.
- Built-in free DDNS, 3G USB Dongle Support.
- Support iPhone, Symbian OS, Blackberry and Android Mobile phone live view
- Supports 2x2TB HDD, 2 USB2.0 slot, supports USB, mouse, backup, upgrade
- Strong Network server, support IE review and CMS(can manager over 64 units DVR)
- Support PTZ control through RS485
- Support HDMI output
- CE, FCC & RoHS Certified

Specification

Value Series

Model	XD168V
Video Input	16 channel, BNC, 1.0Vp-p,75Ω
Audio Input	4 channel,RCA 200-2800mV,30KΩ
Video Output	1 channel, BNC, 1.0Vp-p,75Ω, 1 VGA, & 1 HDMI output
Audio Output	1 channel ,RCA, 200-3000mV,5KΩ
Recording Frame Rate	400fps, (2D1+14CIF)@25fps
HVR	Analog Camera: 4 Ch D1 & Digital Camera: 1 -1080P/ 1 -720P/ 9 Ch. D1/ 8 Ch. 960 H/ 4 Ch. 720P/ 2 Ch. 1080P/ 1-720P/ 7 -D1/ 1-1080P/ 1-720P /2-D1
Video Display	D1 (704x576), CIF (352x288)
Image Compression	H.264
Audio Compression	ADPCM
Recording Resolution	PAL, CIF(352x288)
Alarm In	4ch
Alarm Out	1Ch
Image Quality Setting	Lowest, Lower, Middle, High, Higher, Highest
HDD Quick Cleaning	Quick clean upto 500gb in 25 seconds
Recording Mode	Manual, Alarm, Dynamic Detection, Timing
Detection Area	Zones:396(22*18)detection zones
Motion Detection Sensitivity	Lowest, Lower, Middle, High, Higher, Highest
Pre Alarm Recording	Yes(max 30sec)
Key Lock	Yes
Video Playback	Support 16 channels playback
HDD	Supports 2 SATA port x (max 2048GB SATA HDD)
Backup Mode	Network and USB Flash Drive, CD-DVD/RW(Optional)
USB Interface	1PCS USB 2.0 for backup ; 1PCS USB 1.1 for mouse
VGA Interface	1 VGA out, support resolution :Support 800x600, 1024x768, 1280x720, 1280x1024, 1440x900
Serial Interface	RS-485
Network Interface	RJ-45, 10M / 100M
Power Source	DC12V/4.15A
Mobile Monitoring	Support GPRS/ CDMA/ EDGE/3G
Operation Temperature	0°~50°C
Dimension(W x L x H)	370 X 300 X 6 mm
Certification	CE, FCC & RoHS
Note:	Product appearance & technical specifications are subject to change without any prior notice.