

Value Series

Full D1 DVR



Value Series 4Ch DVR

XD047D1

Xper Value Series Pentaplex DVR provides multi-channel recording with simultaneous playback and viewing. The Xper Value Series DVR can be accessed and controlled from front panel, Network or via a mouse, giving the user full access to all the DVR's features including PTZ control, Alarm and Event Management and Activity Detection.

SALIENT FEATURES

- H.264 High efficiency Video Compression.
- 4CH with total 100fps support D1@25fps/ch.
- 4CH playback.
- Support HDMI output
- Built-in free DDNS, 3G USB Dongle Support.
- Supports iPhone, Symbian OS, Blackberry and Android Mobile phone live view
- Supports 1x2TB HDD, 2 USB2.0 slot, supports USB, mouse, backup, upgrade
- Strong Network server, support IE review and CMS(can manager over 64 units DVR)
- Support PTZ control through RS485
- CE, FCC & RoHS Certified

Specification

Value Series

Model	XD047D1
Video Input	4channel, BNC, 1.0Vp-p,75Ω
Audio Input	4channel,RCA 200-2800mV,30KΩ
Video Output	2 channel, BNC, 1.0Vp-p,75Ω and 1 VGA output & 1 HDMI output
Audio Output	1 channel ,RCA, 200-3000mV,5KΩ
Recording Frame Rate	100fps, 4D1@25fps
Video Display	D1 (704×576)
Image Compression	H.264
Audio Compression	ADPCM
Recording Resolution	PAL, D1 (704×576)
Alarm In	No Alarm
Alarm Out	No Alarm
Image Quality Setting	Lowest, Lower, Middle, High, Higher, Highest
HDD Quick Cleaning	Quick clean upto 500gb in 25 seconds
Recording Mode	Manual, Alarm, Dynamic Detection, Timing
Detection Area	Zones:396(22*18)detection zones
Motion Detection Sensitivity	Lowest, Lower, Middle, High, Higher, Highest
Pre Alarm Recording	Yes(max 30sec)
Key Lock	Yes
Video Playback	Support 4 channels playback
HDD	Support 1 x2TB HDD port (max 2048G)
Backup Mode	Network and USB Flash Drive
USB Interface	1PCS USB 2.0 for backup ; 1PCS USB 1.1 for mouse
VGA Interface	1 VGA out, support resolution :Support 800x600, 1024x768, 1280x720, 1280x1024, 1440x900
Serial Interface	RS-485
Network Interface	RJ-45, 10M / 100M
Power Source	DC12V/4.15A
Mobile Monitoring	Support GPRS/ CDMA/ EDGE/3G
Operation Temperature	0°~50°C
Dimension(W L H)	324 x 243 x 5 mm
Certification	CE, FCC & RoHS
Note:	Product appearance & technical specifications are subject to change without any prior notice.