

# Digital Video Recorder : D1



## Power Series DVR

# XD045D1

Xper Power Series FULL D1 Pentaplex DVR provides multi-channel recording with simultaneous playback and viewing. The Xper Power Series DVR can be accessed and controlled from front panel, Network or via a mouse, giving the user full access to all the DVR's features including PTZ control, Alarm and Event Management and Activity Detection.

## SALIENT FEATURES

- H.264 High efficiency Video Compression.
- 4CH with total 100fps support 4ch 960H@25fps/ch.
- 4CH realtime playback.
- LED display at the front panel show the time, network, alarm,
- Display, power and so on state.
- Built in free DDNS.
- Support Symbian, S60V3/V5, Windows mobile, iphone, Android,
- BlackBerry, mobile phone live view via 3G net
- Support 2TB \*1HDD, with 2 USB2.0 slot, support USB, mouse,
- backup, burning, upgrade
- Strong Network server, support IE review and CMS(can
- manager over 500 units DVR)
- Build in free DDNS
- Support HDMI output (1920 \* 1080)
- Support PTZ control through RS485
- CE, FCC & RoHS Certified

# Specification

# Power Series

Model	XD045D1
Video Input	4channel, BNC, 1.0Vp-p,75Ω
Audio Input	4channel,RCA 200-2800mV,30KΩ
Video Output	1 channel BNC out 1.0Vp-p,75Ω / 1 VGA output / 1 channel HDMI Output (1920*1080P)
Audio Output	1 channel ,RCA, 200-3000mV,5KΩ
Recording Frame Rate	(FPS/Sec):100, 4CH 960H@25FPS
Video Display	960H: 976 (H) × 582 (V)
Image Compression	H.264
Audio Compression	ADPCM
Recording Resolution	PAL, 960H(976×582) , D1(704x576), CIF(352×288)
Alarm In	4ch
Alarm Out	1Ch
Image Quality Setting	Lowest, Lower, Middle, High, Higher, Highest
HDD Quick Cleaning	Quick clean upto 500gb in 25 seconds
Recording Mode	Manual, Alarm, Dynamic Detection, Timing
Detection Area	Zones:396(22*18)detection zones
Motion Detection Sensitivity	Lowest, Lower, Middle, High, Higher, Highest
Pre Alarm Recording	Yes(max 30sec)
Key Lock	Yes
Video Playback	Support 4 channels simultaneous playback
HDD	Supports 2TB *1HDD port x (max 2048GB SATA HDD)
Backup Mode	Network burn, mobile Hard disk and USB burn
USB Interface	1PCS USB 2.0 for backup ; 1PCS USB 1.1 for mouse
VGA Interface	1 VGA out, support resolution :Support 800x600, 1024x768, 1280x720, 1280x1024, 1440x900
Serial Interface	RS-485
Network Interface	RJ-45, 10M / 100M
Power Source	DC12V/4.15A
Mobile Monitoring	Support 3G/WIFI Card
Operation Temperature	0°~50°C
Dimension (W x L x H)	370 x 315 x 55 mm
Certification	CE, FCC & RoHS
Note:	Product appearance & technical specifications are subject to change without any prior notice.