

8ch 1080P Network Video Recorder



8Ch. Network Video Recorder

XDIP08-02

Xper NVR provides multi-channel recording with simultaneous playback and viewing. The Xper NVR can be accessed and controlled from front panel, Network or via a mouse, giving the user full access to all the NVR's features including PTZ control, Alarm and Event Management and Activity Detection.

SALIENT FEATURES

- H.264 High efficiency Video Compression.
- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place.
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard.
- Support megapixel HD network video preview, storage and playback.
- Support search, playback and backup by event.
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream and 4 channels playback.
- Supports monitor PTZ on preview mode.
- Offer CMS for free.
- CE, FCC & RoHS Certified



α				C	Ca				
<u> </u>	n	$\mathbf{\Omega}$	OI	t٦	06	า 1	-	0	n
N	U	て	$\cup 1$	1.1	\mathbf{c}	וג	JΙ	U.	ш
	ш-								

Model		XDIP08-02				
Operating System	1	Embedded LINUX operating system				
Image Code Cont	trol	Image code quality adjustable, variable bitstream optional.				
Dual Stream		Each channel can set main stream and sub stream.				
Video Standard		1080P(1920×1080)30fps/960P(1280×960)/720P(1280×720)30fps				
Monitoring Image Quality		1080P(1920×1080)/960P(1280×960)/720P(1280×720)				
Image Motion Detection		Each screen can set multiple detection areas and set 6-level sensitivity (IPC Support)				
Recording Playback Quality		4ch playback in 8ch 720P mode; 1ch playback in 8ch 1080P/960P mode.				
Region Cover		Every channel can set 4 cover regions (IPC Support)				
Recording Mode		Support manual, auto, motion detection, alarm trigger record mode.				
Backup Support		Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup.				
Recording Storage		Local HDD, network				
		①8 IPC×(1280*960) + substream [640*340] + 8ch 1.0MP simultaneous playback				
	Video Input	②8 IPC×(1280*960) + substream[640*480] + 8ch 1.3MP simultaneous playback				
		③8 IPC×(1920*1080) + substream[640*480] + 8ch 2.0MP simultaneous playback				
		48 IPC×(1920*1080) + substream[720*576] + 8ch 2.0MP simultaneous playback				
	Audio Input	4ch network audio n input				
External Ports	Audio Output	1ch RCA				
	Video Output	1ch VGA + 1ch HDMI				
	Network Port	1 RJ45, 10M/100M self-adaptive LAN port				
	RS485 Port	NA				
	USB Port	3×USB 2.0 ports(one on front panel, two rear panel)				
	Wireless Port	Wi-Fi				
	HDD Port	1 × SATA HDD Port				
HDD	Max Capacity	Each port supports MAX 4TB HDD				
Mobile Surveillance		Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone				
Power Supply		12V2.6A				
Power Consumption		≤25W(without HDD)				
Working Temperature		-10°C∼+55°C				
Working Humidity	,	10%-90%				
Dimension		Equipment: 260mm×220mm×43mm, Packing: 355mm×255mm×88.5mm				
Weight(without HDD)		N.W.: 1.5Kg; With Package:2.6Kg				
Certification		CE, FCC & RoHS				
Note:		Product appearance & technical specifications are subject to change without any prior notice.				