

# IP IR Dome Camera



IP IR Dome Camera

## XIP1.3N-M

Xper XIP1.3N-M produces reach & bright colours with high contract ratio. Extremely high resolution picture enables the user to identify each & every detail. The Camera offers aesthetically brilliant design to match the user interior.

### SALIENT FEATURES >>>

- 1.3MP IR Indoor Metal Dome IP Camera
- 3.6/6.0mm Lens
- 36pcs IR LEDS
- IR Distance: 30 Meters
- Metal Housing
- DC12V Power
- Industrial design and production, precise circuit & structure
- Easy for installation, nice streamline design
- CE, FCC & RoHS Certified

## Specification

Model	XIP1.3N-M
Image Sensor	1.3 Mega Pixel Image Sensor
Horizontal Resolution	1.0 Mega Pixel
Minimum Illumination	Color 0.1Lux@F1.2; B/W 0.01 Lux@F1.2
Lens	3.6mm / 6mm
IR LEDS	36 Pcs.
IR Distance	30 mtr.
Video Process	Support Dual-Stream, AVI Format ; Support Adjustable Stream 0.1M~6Mbps.
Protocol Support	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
Auto Balance	Automatic
Gain Control (AGC)	Automatic
Exposure Control	Automatic
Day & Night Function	With IR-CUT
Compression	H.264
Video Bit Rate	128Kbps ~ 8Mbps
Bit Stream Type	Video Stream
Image Output	Main Stream:1280x960@25fps
	Minor Stream:640*480@25fps
Mobile monitor	Support Mobile Monitoring(Iphone,Windows Mobile,Blackberry,Symbian,Android)
Network Port	1 RJ45 10M/100M Ethernet port
Synchronization	Internal Synchronization
Remote Operation	System Settings, Stream Management, Account Management, Network Management
Motion Detection	Supported
Intellectual Alarm	E-mail Alerts, Alarm Client
Network transmission	P2P Penetrate Automatic Forwarding
Support	Support Multi-Screen software and CMS
Operating Temperature	-10℃~ +55℃
Certifications	CE, FCC & RoHS
Note:	Product appearance & technical specifications are subject to change without any prior notice.